

ENSTO

Reusable connector

SLIW65

Code	SLIW65
GTIN	6438100312695
Name	Reusable connector 1x2.5-35 mm ²
Description	Reusable connectors is specially designed for use with universal piercing connectors e.g. SLIW57 up to 1000 V a.c. Allows service line disconnection without removing a main connector. SLIW65 is for use with aluminium or copper conductors.



Vendor

Technical specification

Others

ETIM Class: EC001062

Certificates

Standards: EN 50483-4:2009

Mechanical

Tightening torque Nm: 11 Nm

Electrical values

Highest system voltage: 1 kV

Test voltage: 4 kV / 50 Hz / 1 min

ETIM 7

Etim

Clamping channel opening branch conductor: One side open

Material branch conductor: Aluminium/copper

Nominal cross section branch conductor SE/RE: 2.5 ... 35 mm²

Nominal cross section branch conductor SM/RM:	2.5 ... 35 mm ²
Surface protection:	Tinned
Terminal insulated:	True
Type of connection:	Screwed connection

Packaging

Pallet package

Unit:	pcs
Package size:	2160
Depth:	1200 mm
Width:	800 mm
Height:	690 mm

Default package

Unit:	pcs
Package size:	60
Depth:	383 mm
Width:	258 mm
Height:	131 mm
Volume:	12.944634 l



Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com