

ENSTO

Reusable connector

SLIW65S

Code SLIW65S
 GTIN 6438100312701
 Name Reusable connector
 1x2.5-35 mm²
 Description Reusable connectors is specially designed for use with universal piercing connectors e.g. SLIW57 up to 1000 V a.c. Allows service line disconnection without removing a main connector. SLIW65S is for use with aluminium or copper conductors

Vendor



Technical specification

Others

ETIM Class: EC001062

Certificates

Standards: EN 50483-4:2009

Mechanical

Tightening torque Nm: 11 Nm

Electrical values

Highest system voltage: 1 kV

Test voltage: 4 kV / 50 Hz / 1 min

ETIM 7

Etim

Clamping channel opening branch conductor: One side open

Material branch conductor: Aluminium/copper

Nominal cross section branch conductor SE/RE:	2.5 ... 35 mm ²
Nominal cross section branch conductor SM/RM:	2.5 ... 35 mm ²
Surface protection:	Tinned
Terminal insulated:	True
Type of connection:	Screwed connection

Packaging

Pallet package

Unit:	pcs
Package size:	3780
Depth:	1200 mm
Width:	800 mm
Height:	1080 mm

Default package

Unit:	pcs
Package size:	60
Depth:	140 mm
Width:	40 mm
Height:	75 mm
Volume:	0.42 l