

ENSTO

Insulation piercing connector

SLIW67

Code	SLIW67
GTIN	6438100317980
Name	Insulation piercing connector 4x6-35 mm ²
Description	Multitap connectors is specially designed for use with universal piercing connectors e.g. SLIW57, SLIW58, SL11.118, SLIP22.1, SLIP22.127 and SLIP32.2 up to 1000 V a.c. to facilitate several out-going conductors. Each branch conductor can be connected with a separate screw.

Vendor



Technical specification

Others

ETIM Class: EC001062

Certificates

Connector class: A1
Standards: EN 50483-4:2009

Mechanical

Tightening torque Nm: 10 Nm

Electrical values

Highest system voltage: 1 kV
Test voltage in water: 6 kV / 50 Hz / 1 min

ETIM 7

Etim

Clamping channel opening branch conductor: Both sides open
Clamping channel opening main conductor: Both sides open

Material branch conductor:	Aluminium/copper
Material main conductor:	Aluminium/copper
Nominal cross section branch conductor SE/RE:	6 ... 35 mm ²
Nominal cross section branch conductor SM/RM:	6 ... 35 mm ²
Surface protection:	Tinned
Terminal insulated:	True
Type of connection:	Insulation piercing connector IPC

Packaging

Pallet package

Unit:	pcs
Package size:	1575
Depth:	1200 mm
Width:	800 mm
Height:	1050 mm

Default package

Unit:	pcs
Package size:	20
Depth:	383 mm
Width:	258 mm
Height:	131 mm
Volume:	12.944634 l



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com