

ENSTO

Terminal clamp

SN3.31



Code	SN3.31
GTIN	6418677416170
Name	Terminal clamp AAAC 50-95 mm ²
Description	SN 3.31 is used for the termination of aluminium conductors to a pole or wall. Equipped with three M8 bolts.
Vendor	

Technical specification

Others

ETIM Class: EC001062

Certificates

Standards: VDE 220 Teil 1/11.71 and Teil 2/11.71,SFS 2663

Features

Bolt: 3xM8

Dimensions

Messenger conductor size: 50 ... 95 mm²
 Messenger diameter: 7.9 ... 11.7 mm
 Weight: 0.18 kg

Mechanical

SMFL: 25.1 kN (95 mm²)
 Tightening torque Nm: 26 Nm

ETIM

Etim

Clamping channel opening branch conductor: Both sides open



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com

Clamping channel opening main conductor:	Both sides open
Material branch conductor:	Aluminium
Material main conductor:	Aluminium
Nominal cross section branch conductor SE/RE:	50 ... 95 mm ²
Nominal cross section branch conductor SM/RM:	50 ... 95 mm ²
Nominal cross section main conductor SE:	50 ... 95 mm ²
Nominal cross section main conductor SM:	50 ... 95 mm ²
Surface protection:	Bare
Terminal insulated:	False
Type of connection:	Screwed connection

Packaging

Pallet package

Unit:	pcs
Package size:	3500
Depth:	1200 mm
Width:	800 mm
Height:	840 mm

Default package

Unit:	pcs
Package size:	50
Depth:	218 mm
Width:	218 mm
Height:	176 mm
Volume:	8.364224 l



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com