

ENSTO

Tension clamp

SO141

Code	SO141
GTIN	6418677404405
Name	Tension clamp
	For AAAC messenger (16)25-95 mm ² Ø(4.8)5.7-11.3 mm
Description	For suspensioning of LV ABC with uninsulated messenger (AMKA). The messenger is fitted, the clamp opened, directly into the groove without cutting. Clamp equipped with eye for cable hoist.SMFL for various messenger cross- sections are as follows: 25 mm ² - 6.6 kN 35 mm ² - 9.3 kN 50 mm ² - 13.2 kN 70 mm ² - 18.6 kN 95 mm ² - 25.1 kN

Vendor



Technical specification

Others

ETIM Class: EC003516

Certificates

Standards: EN 50483-3

Dimensions

Messenger conductor size: 25 ... 95 mm²

Messenger diameter: 5.8 ... 11.3 mm

Weight: 0.46 kg

Mechanical

SMFL: 25.1 kN

Tightening torque Nm: 44 Nm



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com

Etim

Type of accessory: Other

Packaging

Pallet package

Unit: PCE
Package size: 1350
Depth: 1200 mm
Width: 800 mm
Height: 1190 mm

Default package

Unit: PCE
Package size: 25
Depth: 380 mm
Width: 260 mm
Height: 175 mm
Volume: 17.29 l