

ENSTO

Tension clamp

SO28

Code SO28
 GTIN 6418677404580
 Name Tension clamp
 For uninsulated AAAC messenger 25-50 mm²
 Description The messenger is fitted, the clamp opened, directly into the groove without cutting. SMFL various messenger cross-sections: 25 mm² - 6.6 kN, 35 mm² - 9.3 kN, 50 mm² - 13.2 kN

Vendor



Technical specification

Others

ETIM Class: EC003516

Certificates

Standards: EN 50483-2:2009

Dimensions

Messenger conductor size: 25 ... 50 mm²

Messenger diameter: 5.8 ... 8 mm

Weight: 0.25 kg

Mechanical

SMFL: 13.2 kN

Tightening torque Nm: 20 Nm

ETIM

Etim

Type of accessory: Other



THORNE &
DERRICK
 INTERNATIONAL

Thorne & Derrick
 +44 (0) 191 410 4292
www.powerandcables.com

Pallet package

Unit:	pcs
Package size:	2700
Depth:	1200 mm
Width:	800 mm
Height:	1190 mm

Default package

Unit:	pcs
Package size:	50
Depth:	380 mm
Width:	260 mm
Height:	175 mm
Volume:	17.29 l



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com