$RapidSTACK^{\tiny{\mathsf{TM}}}$

RapidSTACK™

Access Chamber Section

1000mm x 1000mm



Product Description

RapidSTACK $^{\mathbb{M}}$ offers a modular, scalable solution made from 150mm deep riser sections which stack to offer flexibility in finished chamber depths.

Product Details

Clear Opening: 1000mm x 1000mm External Dimensions: 1168mm x 1168mm

Stacking Depth: 150mm Actual Depth: 162mm Weight: 23.8kg

Product Code: CPRDRS-10001000
Delivery Options: Assembled Ring or Flatpack



Materials Properties

Material Profile	Glass Reinforced Polyester (GRP)	Grey
Tensile Strength	ISO 527-4	40MPa
Flexural Strength	ISO 14125	70MPa
Impact Strength	ISO 14125	20KJ/m²
Heat Distortion Temperature Range	ISO 75-2	>200°C
Density	ISO 1183	2 g/cm ³
Water Absorption	ISO 62	<0.5
Fire Performance	UL 94	НВ


Installation

RapidSTACK[™] has been tested to withstand vertical loads of EN124 D400. Please refer to the STAKKAbox[™] Installation Guide for installation details.

Key Features

- Fast and easy to install
- Variability in size
- Flat pack option







RapidSTACK™ cross-section top view



Scan for access to technical documents library

CPRDRS-1000×1000 V.01 01/08/2019

