

RapidSTACK™

# RapidSTACK™

## Access Chamber Section

1800mm x 1800mm




### Product Description

RapidSTACK™ offers a modular, scalable solution made from 150mm deep riser sections which stack to offer flexibility in finished chamber depths.

### Product Details

Clear Opening: 1800mm x 1800mm  
External Dimensions: 1968mm x 1968mm  
Stacking Depth: 150mm  
Actual Depth: 162mm

Weight: 19.5kg  
Product Code: CPRDRS-18001800  
Delivery Options: Assembled Ring or Flatpack



### Materials Properties

Material Profile	Glass Reinforced Polyester (GRP)	Grey
Tensile Strength	ISO 527-4	40MPa
Flexural Strength	ISO 14125	70MPa
Impact Strength	ISO 14125	20KJ/m <sup>2</sup>
Heat Distortion Temperature Range	ISO 75-2	>200°C
Density	ISO 1183	2 g/cm <sup>3</sup>
Water Absorption	ISO 62	<0.5
Fire Performance	UL 94	HB

### Installation


RapidSTACK™ has been tested to withstand vertical loads of EN124 D400. Please refer to the STAKKAbOX™ Installation Guide for installation details.

### Key Features

- Fast and easy to install
- Variability in size
- Flat pack option



RapidSTACK™ cross-section detail



RapidSTACK™ cross-section top view



Scan for access to  
technical documents library

CPRDRS-1800x1800 V.01 14/01/2020



THORNE &  
DERRICK  
INTERNATIONAL

Thorne & Derrick  
+44 (0) 191 410 4292  
www.powerandcables.com