

## STAKKAbox™ ULTIMA Connect

## Access Chamber Section

2500mm x 1200mm




## Product Description

STAKKAbox™ ULTIMA Connect offers a modular scalable solution built on-site with easily connectable corner pieces and sidewall lengths. Being used in conjunction additional chamber sizes specified by the contractor can be made.

## Product Details

Clear Opening:	2500mm x 1200mm	Weight:	61kg	Corners:	4 x 1200mm
External Dimensions:	2635mm x 1335mm	Product Code:	CPUCRS-25001200	Sidewalls:	2 x 1000mm
Stacking Depth:	150mm	Delivery Options:	Assembled Ring or Flatpack	Pegs:	6
Actual Depth:	160mm				



## Materials Properties

Material Profile	Glass Reinforced Polyester (GRP)	Grey
Tensile Strength	ISO 527-4	62 MPa
Flexural Strength	ISO 14125	142 MPa
Flexural Modulus	ISO 14125	9.6 GPa
Impact Strength	ISO 179	50 kJ/m <sup>2</sup>
Heat Distortion Temperature Range	ISO 75-2	>200 °C
Density	ISO 1183	1.7 g/cm <sup>3</sup>
Water Absorption	ISO 62	≤0.5%
Volume Resistivity	IEC 60093	1.00E12 ohm.cm
Fire Performance	UL 94	HB to V0
Limited Oxygen Index	ISO 4589-2	27%

## Installation


STAKKAbox™ ULTIMA Connect has been tested to withstand vertical loads of EN124 E600. Please refer to the STAKKAbox™ Installation Guide for installation details.

## Key Features


- Variable in size
- Lightweight
- Fast and easy to install



Scan for access to  
technical documents library



ULTIMA Connect cross-section detail



ULTIMA Connect cross-section top view

CPUC-25001200 V.01 14/01/2019

DISCLAIMER: STAKKAbox™ ULTIMA Connect is a configurable product, thus separate chambers can be constructed using different combinations of component parts. Specific component combinations can be accommodated upon request.