

DENSOSEAL 16A™

A FIRM, FIBROUS
MASTIC FOR THE
SEALING OF SERVICE
ENTRIES AND DUCTS.



Densoseal 16A™ is a self supporting non-setting mastic which has been developed for sealing cable ducts and conduits against gas or water. It has British Telecom type approval and meets the requirements of British Gas for sealing services.

- Adheres to glazed earthenware, steel and unplasticised materials such as lead, polythene or PVC.
- Unaffected by natural gas and water.
- Accommodates movement.
- Adheres to wet surfaces.
- Withstands at least 20kPa (2 metre head) water pressure for a minimum of 30 minutes.

COMPOSITION

A firm fibrous mastic based on polybutene, mineral fillers, organic fibres and water displacing materials. Preformed strip.

FIELD OF APPLICATION

Gas and water can accumulate in underground ducts such as those carrying telephone or electricity supply cables. Where ducts terminate inside buildings, manholes or chambers they must be sealed against gas and water. Densoseal 16A is especially suitable for those applications where ducts are wet or liable to fill with water.

METHOD OF APPLICATION

Densoseal 16A is packed into the ends of the duct by hand and moulded firmly around cables and against the duct ensuring there are no gaps or fissures. The mastic should be packed to a depth at least equal to the diameter of the duct. Surfaces should be free from loose rust, scale, dirt or previous sealants.



PUB No. 428.08.2018



FM 01548 | EMS 583748
BS EN ISO 9001:2015 & 14001:2015



Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com



A MEMBER OF WINN & COALES INTERNATIONAL