

EARTH CLAMPS FOR OVERHEAD LIVE NETWORKS AND SUBSTATIONS

IEC 61230 : 2008 

Copper aluminium bronze earth clamps.



MT-843



MT-843-P



MT-847



MT-852



MT-853

Reference	Rating kA/x s	Use	Connection Ø (mm)	 (mm)	 (mm)	
				Dimension	Clamp capacity	Weight
MT-843	40 kA/1 s	Substation/ Overhead line	Hole : Ø 12.5	45 x 106 x 165	 Ø 6 -25  0 - 35	0.95
MT-843-P	40 kA/1 s	Substation	3 Holes : Ø 12.5	45 x 106 x 165	 Ø 6 -35  0 - 35	0.95
MT-847	25 kA/0.5 s	Overhead line	Hole : Ø 13	45 x 106 x 170	 0 - 30	1.00
MT-852	63 kA/0.5 s	Substation	Hole : Ø 13	70 x 125 x 155	Fixed points	1.40
MT-853	40 kA/0.5 s	Substation	Hole : Ø 13	65 x 130 x 135	Fixed points	1.00

COPPER CABLES

Extra-flexible braided multi-strand copper.
Delivered to the meter with a minimum of 5 meters.
Available in vinyl or silicone sheath.

IEC 61230 : 2008 