



SHORT CIRCUITING DEVICE FOR LV CABINET

The earthing works is a mandatory operation in the NFC 18510 (chp 7.1 - Processes log) standard.

Tinned copper insulated cable silicone core 16 mm².

Authorized employment ENEDIS equipment.

Composition A: for connection.

Composition B: for network.

Composition C: for connection and network. Maximum Icc: 4kA/1s

Reference	Description
MC-296-A	4 multi-strand copper cables 16mm ² MC-296-440 + 1 micro clamps MC-296-P* + 1 connecting blade M-95627/4* + 1 round cartridge M-95626/4* + 1 cartridge size 00 MC-296-00/08* + 1 open end spanners 13/14/16/17 MO-687-D + 1 handle MC-296-M + 1 Case with foam and notice M-91209
MC-296-B	4 multi-strand copper cables 16mm ² MC-296-440 + 5 multi-strand copper cables 16mm ² M-952656 + 1 micro clamps MC-296-P* + 1 cartridge size 115 MC-296-115/08* + 1 cartridge size 160 MC-296-160/08* + 1 threaded adapters MC-181* + 1 pipe wrench 10x17mm M-882462 + 1 open end spanners 13/14/16/17 MO-687-D + 1 handle MC-296-M + 1 case with foam and notice M-91209
MC-296-C	4 multi-strand copper cables 16mm ² MC-296-560 + 5 multi-strand copper cables 16mm ² M-952656 + 5 micro clamps + 1 connecting blade M-95627/4* + 1 round cartridge M-95626/4* + 1 cartridge size 00 MC-296-00/08* + 1 cartridge size 115 MC-296-115/08* + 1 cartridge size 160 MC-296-160/08* + 1 threaded adapters MC-181* + 1 pipe wrench 10x17mm M-882462 + 1 open end spanners 13/14/16/17 MO-687-D + 1 handle MC-296-M + 1 case with foam and notice M-91209
* Sold in packs of 4. Other composition on request.	



IEC 61230 :2008



MC-296-00/08



MC-296-115/08



MC-296-160/08



MC-296-M



M-95626/4



M-95627/4



MC-296-P



Interventions on LV Cabinets.




SHORT CIRCUITING DEVICES FOR LV INDUSTRIAL CABINETS

The earthing works is a mandatory operation in the NFC 18510 (- Processes log chp 7.1) standard.

Composition:


- 5 multi-strand copper cables.
- 5 micro clamps + 1 Case and notice M-76768.


Reference	Section (mm ²)	Icc (kA/1s)
MC-296-NFC-16	16	4
MC-296-NFC-25	25	7
MC-296-NFC-35	35	10


IEC 61230 :2008 


THREADED ADAPTERS

Smooth threaded terminals for positioning shunts ((LV Live working tools) or LV earthing equipment and LV short circuit cabinets terminals.

Reference	Description	Composition (by reference, delivered in a vinyl bag)	
			Weight
MC-184-6F	Smooth threaded terminal M6 female	Set of 4 adapters	120
MC-182	Smooth threaded terminal M8 female	Set of 4 adapters	150
MC-185-10F	Smooth threaded terminal M10 female	Set of 4 adapters	200
MC-183	Smooth threaded terminal M12 female	Set of 4 adapters	250

Reference	Description	Composition (by reference, delivered in a vinyl bag)	
			Weight
MC-184-6M	Smooth threaded terminal M6 male	Set of 4 adapters	120
MC-182-8M	Smooth threaded terminal M8 male	Set of 4 adapters	150
MC-185-10M	Smooth threaded terminal M10 male	Set of 4 adapters	200
MC-181	Smooth threaded terminal M12 male	Set of 4 adapters	250



MC-182

MC-183



MC-181

IEC 61230 :2008 