

# MV-CONNEX Cable Joint, size 1 up to 36 kV, not insulated against soil

For outdoor, offshore and underground application.

**Caution:**

For use underground or offshore the bell flanges of the separable connectors must be made of bronze.

Single-pole, resistant to outdoor, soil-resistant, offshore-proof, plug-in type.

The single-pole connection joint is supplied as factory-built, the contact bushings are integrated into the soil-resistant insulating body. The connection is established by inserting the CONNEX separable connector.

**The soil sensitivity is given by the contact of the bell flange with the soil.**



*Picture may vary.*

## Technical Data

<b>Article no.</b>		<b>827 212 001</b>
<b>Size</b>		<b>1</b>
<b>Max. system voltage</b>	<b>U<sub>m</sub> (kV)</b>	<b>36</b>
<b>Design</b>		<b>straight</b>
<b>Nominal current</b>	<b>I<sub>N</sub> (A)</b>	<b>630</b>
<b>Weight</b>	<b>(kg)</b>	<b>5,8</b>
<b>Size</b>		<b>1</b>
<b>Max. system voltage</b>	<b>U<sub>m</sub> (kV)</b>	<b>36</b>
<b>Design</b>		<b>straight</b>
<b>Nominal current</b>	<b>I<sub>N</sub> (A)</b>	<b>630</b>
<b>Diameter</b>	<b>(mm)</b>	<b>143</b>

## Dimensions

<b>Diameter</b>	<b>(mm)</b>	<b>143</b>
<b>Length</b>	<b>(mm)</b>	<b>263</b>
<b>Length</b>	<b>(mm)</b>	<b>263</b>