

Certifications

EN 60900 - Approved by ENEDIS

Section

LV Live working

Application

Field
Laboratory
Production



PRODUCT BENEFITS

Made of insulating material

Safety, light and easy to use

TOOL CAPACITY

Diameter 26 - 52 mm
1,024 - 2,047 inch

Circular cutting thickness capacity 2,0 mm / 0,079 in

Longitudinal cutting thickness capacity 2,0 mm / 0,079 in

TOOL DIMENSIONS

Length 265 mm

Width 97 mm

Height 73 mm

Weight without box 0,44 Kg

Packaging Box

Composite plier for LV cable

TO DO WHAT

The PG3EC/2020 enables the user to make a circular and longitudinal cut in order to remove cable's outer sheath

PG3EC/2020 for cable Ø26 to 52 mm / 1,023 to 2,047 in (3x50² + 1x50² à 3x240 + 1x95²)



Options

SGM - Large size pouch

Spare part

MTC3E/20 - Spare blade for circular cutting 2,0 mm / 0,079 in (x4)

MTL3E/20 - Spare blade for longitudinal cutting 2,0 mm / 0,079 in



**THORNE &
DERRICK
INTERNATIONAL**

Thorne & Derrick

+44 (0) 191 410 4292

www.powerandcables.com

LV cables Tools

PG3EC/2020



Part Number	Diameter	Tool capacity		Dimensions			Packaging
		Circular cutting thickness capacity	Longitudinal cutting thickness capacity	Length	Width	Height	
PG3EC/2020	26 - 52 mm 1,024 - 2,047 in	2,0 mm / 0,079 in	2,0 mm / 0,079 in	265 mm 10,433 in	97 mm 3,819 in	73 mm 2,874 in	box



THORNE &
DERRICK
INTERNATIONAL

Thorne & Derrick
+44 (0) 191 410 4292
www.powerandcables.com