

Certifications

Approved by ENEDIS

Section

LV

Application

Field



PRODUCT BENEFITS

Oscillating cable support for a better guidance
Stripping of sectoral phases of network cable

Longitudinal head with 3 penetrations to adapt to different thickness of sheath
Interchangeable longitudinal heads for a better versatility

TOOL CAPACITY

Diameter	10 - 30 mm 0,394 - 1,181 inch
Circular cutting thickness capacity (mm / inch)	1,2 mm / 0,047 in
Longitudinal cutting thickness capacity (mm / inch)	1,2 - 1,6 - 1,8 mm / 0,047 - 0,063 - 0,070 in

TOOL DIMENSIONS

Length	260 mm
Width	90 mm
Height	80 mm
Weight without box	0,58 Kg
Packaging	Box

ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE
FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

LV interchangeable 3 penetration pliers for connection cable

TO DO WHAT

The PINTEL4BT/1216-R removes the outer sheath for power off working
Cutting depths are adapted to others connection cable
Circular cutting depth : 1,2 / 1,6 / 1,8 mm / 0,047 / 0,063 / 0,070 in



Options

TRL - 3 penetrations
TRL - 1 penetration
SGM - Large size pouch

Spare part

MTCP4/12 - Spare blade for circular cutting 1,2 mm / 0,047 in (x3)
TRL/12-16-18 - Spare interchangeable longitudinal cutting head

Associated tool

PINTEL4BT/1216 - Stripping pliers for Low-Voltage secondary distribution cable's outer jacket
PINTEL4BT/1216R1000V - Live line stripping pliers for Low-Voltage sec distribution cable's outer jacket

LV cables Tools

PINTEL4BT/1216-R



Part Number	Diameter	Tool capacity		Dimensions			Packaging
		Circular cutting thickness capacity (mm / inch)	Longitudinal cutting thickness capacity (mm / inch)	Length	Width	Height	
PINTEL4BT/1216-R	10 - 30 mm 0,394 - 1,181 in	1,2 mm / 0,047 in	1,2 - 1,6 - 1,8 mm / 0,047 - 0,063 - 0,070 in	260 mm 10,236 in	90 mm 3,543 in	80 mm 3,150 in	box