

DS DECONTACTOR is a compact and waterproof plug and socket-outlet with integrated switch for industrial purposes.

DS DECONTACTOR complies with the following regulations and standards(a):

European Directives Low Voltage and RoHS (affixing of CE marking), REACH European Regulation, standards IEC/EN 60309-1, IEC/EN 60309-4, IEC/EN 60947-3 (dealing with the load breaking capacities AC-22 and AC-23), UL 1682, UL 2682 (USA), CSA C22.2 N° 182.1-07 (Canada), GB/T 11918.1 (China).

DS DECONTACTOR is certified by the following certification bodies:

LCIE (France), UL (USA), SAA (Australia), VDE (Germany), TR CU (Russia), CSA (Canada), CQC (China).



The use of DS DECONTACTOR facilitates the compliance with:

- electrical machinery to the "Machinery" European Directive on isolating device, and to standard EN 60204-1 : Safety of machinery-electrical equipment of machines
- electrical installation:

* to national regulations relating to the improvement of the safety and health of workers at work in France, Italy, Spain, Belgium,

* to installation standards : IEC 60364 (international), HD 60364 (European), NFPA 70 (USA) and NF C 15-100 (French) or other national transposition of IEC/HD 60364.

General information

	DS1	DS3
(b) I_n	30 A	50 A
U_{max} (V AC/V DC)	690/1 000	1 000/1 500
(c) Frequency (Hz)	≤ 500	≤ 500
(d) Number of contacts	4P+E	4P+E
(e) Number of keying positions	24	24
Connection (min - max): mm ²		
Flexible conductors (Cu): main contacts	2.5 - 6	6 - 16
Rigid/stranded conductors (Cu): main contacts	2.5 - 10	10 - 25
Tightening torque - main contacts	1.5 Nm	1.8 Nm
Wiring lugs	Option	Option
Icc: conditional short circuit current (kA)		
with gG fuse	10 kA	10 kA
with RK1 NTD fuse	100 kA	100 kA

Auxiliaries / pilots contacts

I_n	30 A	16 A
U_{max} (V AC/V DC)	500 V	400 V
(f) Number of auxiliaries / pilots contacts	2 aux	4 aux
Connection (min - max): mm ²		
Flexible wiring	2.5 - 6	1 - 2.5
Stranded wiring	2.5 - 10	1.5 - 4
Tightening torque	1.5 Nm	0.8 Nm

Used as connector according to IEC/EN 61984: In

I_n	30 A	50 A
U_{max}	690 V AC	1000 V AC
	1000 V DC	1500 V DC

Breaking as plug and socket-outlet according to IEC/EN 60309-1

(g) I_n (A) / U_{max} (V AC)	30 - 690	50 - 690
----------------------------------	----------	----------

Breaking as switch according to IEC/EN 60947-3

(g) Category AC-22A: I_n (A) - U_{max} (V AC)	32 - 690	40 - 690
(g) Category AC-23A: I_n (A) - U_{max} (V AC)	32 - 480	50 - 400

Breaking as plug and socket-outlet according to UL 2682

Power: HP	15	25
-----------	----	----

Increase of DC load-breaking capacity (contacts in series)

	Option	Option
--	--------	--------

Number of operations


According to IEC/EN 60309-1 : $\cos(\Phi)$ 0,6	2 000	2 000
According to UL 2682 : $\cos(\Phi)$ 0,75	6 000	6 000

Isolating distance

	8 mm	13 mm
--	------	-------

Thermal features

Temperature of use mini/maxi (°C)	-40/+60 °C	-40/+60 °C
Storage temperature mini/max: (°C)	-40/+80 °C	-40/+80 °C
Maximal temperature rise (Kmax):	38 K	30 K
Time constant (to reach 63 % of Kmax)	21mn	23 mn




V : Contact spring

W : Arc chamber

X : Ejection spring


Y : Ejection ring



Contacts with silver nickel alloy tips (Ag/Ni : 85/15)



Spring assisted terminal:
Stainless steel ring



Contacts in series

Mechanical features

- (h) IP: connected device
IP: lid/cap closed
IP: socket-outlet with lid/cap opened

- (i) IK
Retaining/releasing device
(j) Casing

Standard color
Other colors

- Vibrations resistance
Resistance to chemical agents
Protection against UV (according to UL 746C or equivalent)
Salt mist resistance
Screws and bolts
Weight of inlet without accessory (≈)
Weight of socket-outlet without accessory (≈)

Main options

- Socket-outlet opening up to 180°
Self-returning lid

- Inlet cap
Self-returning inlet lid
Locking / padlocking
Automatic self-ejection
Larger release button ("STOP")
Finger draw plates
Industrial-domestic adapter

Mounting accessories

- Poly sleeve: angle (°) 30/70 30/70
Metal sleeve: angle (°) 0/30 0/30/70
Poly box: angle (°) 30 30
Metal box: angle (°) 20 20
Poly box + poly sleeve: angle (°) 70 70
Metal box + poly sleeve: angle (°) 30 30
Metal box + metal sleeve: angle (°) 0/30 0/30/70
Poly straight handle with built-in cable gland: range take (mm) 5 - 21 10 - 30
Threaded poly straight handle M20 - M40 M20 - M40
Threaded metal straight handle M20 - M32 M20 - M40
Poly straight handle + separated poly cable gland: range take (mm) 5 - 32 9 - 32
Metal straight handle + separated metal cable gland: range take (mm) 7 - 23 7 - 32

Spare parts

- Inlet or socket-outlet interior moulding
Inlet or socket-outlet contacts
Inlet or socket-outlet colored gasket
Inlet or socket-outlet casing
Socket-outlet casing gasket

Catalog: [Web link](#)

DS1

IP54

IP55

IP4X - Safety shutter

IK09

Red release button
GRP (poly)

MARECHAL® Blue
On request

✓

✓

Contact us

f1

f1

> 50 000 h

Stainless steel

0.15 kg

0.20 kg

0.26 kg

0.35 kg

Included

IP55

IP66/IP67

IP55

IP55

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

DS3

IP54

IP55

IP4X - Safety shutter

IK09

Red release button
GRP (poly)

MARECHAL® Blue
On request

✓

✓

Contact us

f1

f1

> 50 000 h

Stainless steel

0.15 kg

0.20 kg

0.26 kg

0.35 kg

Included

IP55

IP66/IP67

IP55

IP55

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓

✓


✓

✓


✓

✓

✓




Dimensions




mm	DS1	DS3
A	15	17
B	166	179
C	69	80
E	48	55

Finger draw plates



Poly straight handle with built-in cable gland



- (a) European Regulation REACH: registration, evaluation, authorisation and restriction of chemicals
IEC/EN 60309-1 : "Plugs, socket-outlets and couplers for industrial purposes – Part 1: General requirements"
IEC/EN 60309-4 : "Plugs, socket-outlets and couplers for industrial purposes – Part 4: Switched socket-outlets and connectors with or without interlock"
IEC/EN 60947-3 : "Low-voltage switchgear and controlgear – Part 3: Switches, disconnectors, switch-disconnectors and fuse-combination units"
IEC/EN 61984 : "Connectors – Safety requirements and tests"
UL 1682 : "Plugs, Receptacles, and Cable Connectors of the Pin and Sleeve Type"
UL 2682 : "Outline of Investigation for Switch-Rated Plugs and Receptacles"
CSA C22,2 No 182,1-07 : "Plugs, Receptacles, and Cable Connectors of the Pin and Sleeve Type"
GB/T 11918.1 : "Plugs, socket-outlets and couplers for industrial purposes – Part 1: General requirements"
- (b) In : Rated current as defined by the manufacturer
(c) Other frequency: contact us
(d) Contacts with silver-nickel tips (Ag/Ni 85/15)
(e) Number of voltage / frequency / grid, keying positions
(f) Auxiliaries contacts are located on the plug and socket-outlet sides. Pilot contacts are only located on the socket-outlet side.
(g) For direct current applications : contact us
(h) IP : Degrees of protection provided by enclosures (IEC/EN 60529)
(i) IK : Degrees of protection provided by enclosures against mechanical impacts (IEC/EN 62262)
(j) GRP : Glass-reinforced technical plastic