

CAT'ARC 25-40 cal/cm² range GATTU AFG-4xx-series, AFG-HOOD-series, KIT-ARC-D-01-series



CAT'ARC kits offer optimized multi-risk and flash arc protection thanks to many advanced features:

- an anti-panic zip allowing the jacket or switching jacket to be quickly removed in the event of an accident,
- a universal solution 25-40 cal/cm²,
- improved comfort and durability:
 - o light and soft fabric with Kermel,
 - comfort padding at the knees,
 - reinforcement at the crotch.

^{*} Be careful, the switching jacket protects the covered areas



AFG-4xx-series, AFG-HOOD-series, KIT-ARC-D-xx-series

TECHNICAL FEATURES

HOOD

- Face shield clips for visor helmet with side slots
- Gray protective shield for better color recognition
- Quick identification of the protection provided by the marking on the outside of the cap

JACKET

- High collar
- 1 chest loop
- 2 chest pockets flap and scratch closure
- 2 lower pockets covered by flap
- Cuffs can be tightened by scratch
- Central closure with red anti-panic zip and double flap for inner and outer protection
- Elasticated belt on the sides
- Standard pictograms on the left sleeve

TROUSERS

- Elasticated belt with loops
- Central closure with jeans button and red zipper
- 2 Italian pockets covered by flap
- 2 cargo pockets flap and scratch closure
- Reinforcements at the crotch
- Comfort foam at the knees
- Adjustable inner leg length (77 cm or 82 cm)

SWITCHING JACKET

- High collar
- 1 chest loop
- 2 chest pockets flap and scratch closure
- 2 lower pockets covered by flap
- Cuffs can be tightened by scratch
- Central closure:
- On the upper part with red anti-panic zip and double flap of protection inside and outside,
- On the lower part, with scratch
- Standard pictograms on the left sleeve









FABRIC

Composition: 70% Kermel / 29% polyester / 1% fil anti-static.

Weight: 425 g/m² Main color: grey black



AFG-4xx-series, AFG-HOOD-series, KIT-ARC-D-xx-series

STANDARD REFERENCES



Standard	Protection	Hood	Jacket	Pant.	Swit. jacket
IEC 61482-2	Arc Protection Class: APC 2 (7 kA). Arc Thermal Performance Value (ATPV): 40 cal/cm ² .	x	x	x	x
ISO 11612	A: Limited flame spread properties B1: Protection against convective heat C2: Protection against radiant heat F2: Protection against contact heat		х	x	x
ISO 11611	Protective clothing for use in welding and allied processes Class 2		x	х	
EN 1149-5	Electrostatic dissipative protective clothing		x	x	x


TO PLACE AN ORDER

Reference	Designation	Composition	Available sizes
AFG-HOOD-4	CAT'ARC hood APC 2 ATPV 25-40	1 textile hood with gray protective	US
	cal/cm²	face shield	
AFG-HOOD-4-KIT	CAT'ARC kit with hood APC 2	1 hood AFG-HOOD-4	US
	ATPV 25-40 cal/cm ² and helmet	1 electrician helmet MO-182/1-B	
AFG-4000-*	Jacket CAT'ARC APC 2 ATPV 25-40	1 jacket	XS – 5XL
	cal/cm²		
AFG-4001-*	Trousers CAT'ARC APC 2 ATPV 25-	1 trousers	XS – 5XL
	40 cal/cm ²		
AFG-4300-*	Switching jacket CAT'ARC APC 2	1 switching jacket	S, L, 2XL, 4XL
	ATPV 25-40 cal/cm ²		
KIT-ARC-D-01-JP-*	CAT'ARC kit APC 2 ATPV 25-40	1 hood AFG-HOOD-4	XS – 5XL
	cal/cm ² with jacket, trousers and	1 electrician helmet MO-182/1-B	
	hood	1 safety glasses MO-11000	
		1 jacket AFG-4000-*	
		1 trousers AFG-4001-*	
		1 carrying bag M-87295	
KIT-ARC-D-01-SJ-*	CAT'ARC kit APC 2 ATPV 25-40	1 hood AFG-HOOD-4	S, L, 2XL, 4XL
	cal/cm ² with switching jacket and	1 electrician helmet MO-182/1-B	
	hood	1 safety glasses MO-11000	
* To be completed with the chosen size - see selection chart below.		1 switching jacket AFG-4300-*	
		1 carrying bag M-87295	



AFG-xxx-series, AFG-HOOD-series, **KIT-ARC-xxx-series**

SIZE CHART



LONG JACKET								' '	
Size to order		S		L		2XL		4XL	
A - Maximum chest measurement (cm)		94		101		109		117	
C - Maximum hip measurement (cm)		94		102		110		117	
The chest measurement defines the size of the garment as long as the hip measurement is less than or equal to the measurement shown in the table. If not, choose the next size up.									

^{*}Measures given in cm