



# Light Duty Quick Adaptable Barrier

Data Sheet v1.0



# Confined Space Safety

## Light Duty Quick Adaptable Barrier

### Description

Confined space entry hazards are severe risks for employees. Accidents with unauthorized confined space entries are often deadly. Light Duty Quick Adaptable Confined Space Barrier is the ideal tool for employees and contractors to secure these dangerous openings. The barrier warns co-workers for its dangers and prevents unauthorized (or accidental) entry.

### Technical information

**Size:** 400 mm

- > **Weight:** 0,440 kg
- > **Min diameter:** 500 mm
- > **Max diameter:** 980 mm

**Size:** 620 mm

- > **Weight:** 0,600 kg
- > **Min diameter:** 750 mm
- > **Max diameter:** 1200 mm

**Size:** 780 mm

- > **Weight:** 0,820 kg
- > **Min diameter:** 930 mm
- > **Max diameter:** 1420 mm

### Signs

Sign 2 is available in NL (Dutch), FR (French), GB (English), ESP (Spanish) and IT (Italian)




# Confined Space Safety

## Light Duty Quick Adaptable Barrier

MODEL	CHARACTERISTICS
<b>Light Duty Quick Adaptable Barrier</b>	<ul style="list-style-type: none"> <li>• 3 sizes available (400 mm, 620 mm and 780 mm)</li> <li>• Light weight</li> <li>• Made from Plastic PE</li> <li>• Holes arms 5 x 2 cm</li> <li>• Connection arms to warning sign M10 Locknut – M10 Bolt</li> <li>• Installation standard bolts or cable ties</li> <li>• Easy installation</li> <li>• Different signs available</li> <li>• Custom signs available from 25 pieces or more</li> </ul>

\* Minimum order quantity of 5 pieces



# OUR WORK AREA



CableSafe® / Westmark  
B.V Arnhemseweg 87  
3832 GK Leusden

