

C-821 HYDRAULIC UNIVERSAL WINCH



The CBS 821 Universal Winch offers the constant pulling tension of a double capstan drive and the flexibility of a direct drive drum in one machine.

The winch employs a powerful petrol engine mounted with associated hydraulics on a sturdy trailer unit. Precise hydraulic controls allow easy operation through one fail-safe lever.

Ideally suited for ABC erection, 11/33kV stringing work, conductor recovery, and underground cable handling.



OPTIONAL EXTRAS

C-821-02	700mm diameter drum fitted with 400m of 8mm Paraline Rope
C-A1-680-27	Split Drum
C-821-14	Waterproof cover

SPECIFICATIONS

Speed	0-30m/min from capstans 0-100m/min drum drive when connected to capstan drive shaft
Drive	Fixed displacement pump and motor through double capstan drive module
Controls	Fail-safe, bi-directional section, creep & inching facility, and operator adjustable load limiting control
Rope Layer	Semi-automatic
Load Indicator	Calibrated gauge dial read out in kg with adjustable limit control
Hydraulic Circuit	Open circuit with double filtration protection
Length	2844mm (Overall)
Width	1420mm
Height	1480mm (With cover)
Weight	455kg (Unladen)
Rope Drum - Empty	22kg
Split Drum	23kg
Frame & Cover	50kg
400m Drum	27kg
600m Drum	40kg

ORDERING INFORMATION

C-821	Hydraulic Universal Winch
-------	---------------------------