## C-821 PORTABLE HYDRAULIC WINCHING SYSTEM



Designed to provide a fully portable winching system, by breaking down into easily transportable modules.

Ideally suited for overhead line stringing work such as ABC conductors, bare conductors or re-conductoring projects, it provides a flexible system suitable where access is restricted and ground disturbance is undesirable.

The winch can be pole mounted or ground mounted using the optional frame. The C-825 Hydraulic Winch comprises of a strong lightweight pole mounting frame with securing chains and incorporates a hydraulic drive and control lever.

## **HYDRAULIC POWER PACK**



This unit is powered by air-cooled, 8hp petrol driven engine, delivering 20 litres/min at a working pressure of 138 bar from the hydraulic circuit. The circuit is protected with return line and filters. CE suction approved.

SPECIFICATIONS		
Output Torque	615Nm / Avg. Tension 300kg	
Speed Control	Fail-safe. Bi-directional section, creep and inching facility	

ORDERING INFORMATION	
C-825-01	Pole Mounted Hydraulic Winch with layering arm
C-1204-1	Hydraulic power pack with 7m hoses

OPTIONAL EXTRAS	
C-821-02	700mm diameter drum fitted with 400m of 8mm Paraline Rope
C-821-03	700mm diameter drum fitted with 600m of Paraline Rope
C-A1-680-27	Split drum for retrieving old conductor
C-825-07	Split drum (Outboard type)
C-825-06	Grounding frame and anchor rods
C-825-09	Carrying handle for hydraulic motor

SPECIFICATIONS		
Length	720mm	
Width	530mm	
Height	615mm	
Weight	66kg	
Hydraulic Tank Capacity	5 Litres	