


MDIII Duct & Conduit Sealing System



Duct sealing systems MDIII have been developed to provide an effective and simple solution for Gas and Watertight sealing of cables & pipes in ducts, conduits & boreholes.

This duct sealing system is extremely flexible and can be installed in ducts vertically and horizontally.

All our duct sealing systems are specified and used by major Electrical, Gas, & Water Utility companies in the UK and Benelux countries.

Complies with 2011 NEC Articles 225.27, 230.8, 300.5(G), 300.7 (A) on Raceway Seals, and 501.15 (B)(2)

Features

- Gas and Watertight 1.0 bar (14.50psi)
- Can be made Fire resistant by using MD+
- Resistant to Hydrogen Sulphide / Methane and many other Gases
- Resistant to Hydrocarbons
- Complies with ATEX regulations
- WIMES Compliant, (3.02 2013 clause 6.4.3.2 c)
- Complies with 2011 NEC Articles 225.27, 230.8, 300.5(G), 300.7 (A) on Raceway Seals, and 501.15 (B)(2)
- Suitable for ducts/conduits & boreholes up to 250mm (10.0" inches)
- Quick and easy installation
- A complete kit for one duct. No wastage
- Seals all know materials, PVC & PE sheathed cables, PILC, (HD) PE pipes
- Excellent mechanical strength, after curing resistant to movements, shocks and vibrations
- Suitable for renovations, can be installed retrospectively
- Over 30 years of operational experience



Specifications

MDIII Duct & Conduit Sealing System

Properties	Unit	Value
Start time expansion	seconds	> 95
End time expansion	minutes	15
Compressive strength	N / cm ²	> 60
Gas and water tightness 1,0bar	30 days	no leakage
Density 10m water column	30 days	no leakage
Volume consistency	cube 10 x 10cm	no change
Temperature Cycles, -20°C tot +40°C	10 consecutive cycles	no leakage
Vibration test 10 Hz/amplitude 3mm	240 hours	no leakage
Axial tensile force	diameter x 10 N	no leakage
Resistance to bending	cables 45° in 2 directions >250mm	no leakage
Expansion polyurethane foam in pipe	cm	< 40
Temperature resistance	°C	+120
Chemical resistance		
0,1N Na ₂ SO ₄	30 days	no degradation
0,1N NaCl	30 days	no degradation
0,1N H ₂ SO ₄	30 days	no degradation
0,1N NaOH	30 days	no degradation
Diesel	30 days	no degradation
Gasoline	30 days	no degradation
Resistance		
Moulds		good
Rodents		good
Shelf life	months	minimal 30

MDIII Duct & Conduit Sealing System

MDIII Duct & Conduit Sealing System

More info

Products

Art.nr.	Product Name	Duct diameter min.-max. (mm)	Maximum cable diameter in the duct (mm)	Order unit
282550P	MDIII-50 duct sealing kit (2.0")	Ø 50 max.	Ø 20 max.	per piece
282575	MDIII-75 duct sealing kit (3.0")	Ø 75 max.	Ø 40 max.	per piece
280295	MDIII-110 duct sealing kit (4.0")	Ø 110 max.	Ø 80 max.	per piece
280296	MDIII-160 duct sealing kit (6.0")	Ø 160 max.	Ø 130 max.	per piece
2802973	MDIII-200 duct sealing kit (8.0")	Ø 200 max.	Ø 160 max.	per piece
2802978	MDIII-250 duct sealing kit (10.0")	Ø 250 max.	Ø 220 max.	per piece