





LINK BOX TECHNICAL DATA SHEET

Drw. No. 08.08.04 Article No. 010404001/0

 Issued Date:
 10.05.2019

 Rev. Date:
 12.08.2021


 Rev.
 01

Туре	LB. W . E .3SA . 3 . 1		
- Description	Three Phase Earthing Link Box with SVL for Single Cable		
- Designation	Wall Type		
- Bonding	Earthing		
- Sheath Voltage Limiter	qty 3		
- Phase No.	3		
Earth	1		
Drawing Number	08.08.04		
- Article No	010404001/0		
Electrical Characteristics			
- Rated Frequency	50/60 Hz		
- SVL Type (*)	Up to 18 kV / Optional		
Protection Class	IP 66		
Material			
- Enclosure	Stainless Steel AISI304 (AISI316 optional)		
- Body Thickness (**)	2 mm		
- Cover Thickness	3 mm		
- Connection Links	10 μm Tinned Electrolytic Copper		
- Connection Links Dimension	50x10 mm (500 mm2)		
- Gasket	Silicone		
- Cable Glands	4x48 mm Silicone gasket & EPR tape		
- Cable Glands Insulation			
- Insulation	Epoxy Support Insulator		
- Conductor Fixing	Conductor Flexconn - 400-500 mm2		
- Painting Process	Electro Static Polyester Powder Paint		
- Painting Code	RAL 7032		
- Labeling Material	Stainless Steel		
- Protection Cover	PET-G		
AC Impulse Test			
- Phase-to-Phase	75 kV		
- Phase-to-Earth	37,5 kV		
Voltage Withstand Test			
- AC	20 kV/1 min		
- DC	25 kV/5 min		
Short Circuit Test			
- Symmetrical	N/A		
Internal Power Arcing Test (Symmetrical)	40 kA/0.1 sec		
	40 K-V0.1 300		

^{*} In case of mismatch in given values, technical drawing provided along with the Order Confirmation is valid. Ask for conformity if SVL is out of EMELEC's scope.

^{**} Body Thickness might differ related to technical drawing revision. For exact value, refer to technical drawing provided along with the Order Confirmation


Bonding Cable



Ø. √1

Schematic Diagram

√ Iø



Enclosure Dimensions (*)

Width	800 mm		
Length	650 mm		
Heigth	390 mm		
Weigth	66 kg		
Filling Compund (Optional)			
Volume	N/A		

^{*} Scheme and dimensions are not to be mentioned as final drawing. For exact dimensions, refer to technical drawing provided along with the Order Confirmation

 $^{^{\}star\star}$ Given are approximate values. Actual values might sligthly differ.