





## **LINK BOX TECHNICAL DATA SHEET**

Drw. No. 10.04.03 Article No. 12403001/0

 Issued Date:
 10.05.2019

 Rev. Date:
 12.08.2021


 Rev.
 03

Туре	LB. U . CB .3SA . 3 . 1	
- Description	Three Phase Cross-Bonding Link Box for Coaxial Cable	
- Designation	Underground	
- Bonding	Cross-Bonding	
- Sheath Voltage Limiter	qty 3	
- Phase No.		
Earth	1	
Drawing Number	10.04.03	
- Article No	12403001/0	
Electrical Characteristics		
- Rated Frequency	50/60 Hz	
- SVL Type (*)	Up to 10 kV / Optional	
Protection Class	IP 68	
Material		
- Enclosure	Stainless Steel AlSl304 (AlSl316 optional)	
- Body Thickness (**)	3 mm	
- Cover Thickness	3 mm	
- Connection Links	10 μm Tinned Electrolytic Copper	
- Connection Links Dimension	40x10 mm (400 mm2)	
- Gasket	Silicone	
- Cable Glands	3x76 mm & 1x48 mm	
- Cable Glands Insulation	Silicone gasket & EPR tape & Mastic Tape & Heat Shirinkable Tube	
- Insulation	Epoxy Support Insulator	
- Conductor Fixing	Coaxial Flexconn - 95-400 mm2	
- Painting Process	Electro Static Polyester Powder Paint	
- Painting Code	RAL 7032	
- Labeling Material	Stainless Steel	
- Protection Cover	PET-G	
AC Impulse Test		
- Phase-to-Phase		
- Phase-to-Earth	40 kV	
Voltage Withstand Test		
- AC	20 kV/1 min	
- DC	25 kV/5 min	
Short Circuit Test		
- Symmetrical	50 kA/1sec	
Internal Power Arcing Test (Symmetrical)	40 kA/0.1 sec	


<sup>\*</sup> In case of mismatch in given values, technical drawing provided along with the Order Confirmation is valid. Ask for conformity if SVL is out of EMELEC's scope.

<sup>\*\*</sup> Body Thickness might differ related to technical drawing revision. For exact value, refer to technical drawing provided along with the Order Confirmation

## Bonding Cable



## Schematic Diagram



## Enclosure Dimensions (\*)

Width	690 mm	
Length	670 mm	
Heigth	334 mm	
Weigth	87 kg	
Filling Compund (C	ptional)	
Volume	55 lt (**)	

<sup>\*</sup> Scheme and dimensions are not to be mentioned as final drawing. For exact dimensions, refer to technical drawing provided along with the Order Confirmation

<sup>\*\*</sup> Given are approximate values. Actual values might sligthly differ.