





## LINK BOX TECHNICAL DATA SHEET

Drw. No. 19.04.02 Article No. 23202001/0

 Issued Date:
 4.08.2021

 Rev. Date:

 Rev.
 00

Туре	LB. MV . E 6 . 1					
- Description	Medium Voltage Earthing Link Box for Single Cab					
- Designation	Undergrou					
- Bonding	Earthin					
- Sheath Voltage Limiter	N <sub>i</sub>					
- Phase No.						
Earth	19.04.02					
Drawing Number						
- Article No	23202001					
Electrical Characteristics						
- Rated Frequency	50/60 H					
- SVL Type (*)	N <sub>i</sub>					
Protection Class	IP (					
<b>M</b> aterial						
- Enclosure	Stainless Steel AISI304 (AISI316 optional					
- Body Thickness (**)	2 m					
- Cover Thickness	2 m					
- Connection Links	Connection Links     10 μm Tinned Electrolytic Copp       Connection Links Dimension     30x3 (90 mm)					
- Connection Links Dimension						
- Gasket	Silicon					
- Cable Glands	7x21 mm					
- Cable Glands Insulation	Silicone gasket & EPR tape & Mastic Tape & Heat Shirinkable Tut					
- Insulation	Epoxy Support Insulat					
- Conductor Fixing	Cable Lug - Max. 50 mm2					
- Painting Process	Electro Static Polyester Powder Pai					
- Painting Code	RAL 703					
- Labeling Material	Stainless Ste					
- Protection Cover	N.					
AC Impulse Test						
- Phase-to-Phase	N/A k					
- Phase-to-Earth	17,5 k					
/oltage Withstand Test	40 1944					
- AC	10 kV/1 m					
- DC	15 kV/5 m					
Short Circuit Test	15 kA/1s					
- Symmetrical	IJ KAJIS					
nternal Power Arcing Test (Symmetrical)	10 kA/0.1 s					
mornari oriel Archig rest (Oynimetrical)	10 KM0.136					

<sup>\*</sup> In case of mismatch in given values, technical drawing provided along with the Order Confirmation is valid. Ask for conformity if SVL is out of EMELEC's scope.


<sup>\*\*</sup> Body Thickness might differ related to technical drawing revision. For exact value, refer to technical drawing provided along with the Order Confirmation

## **Bonding Cable**

- Type									Single
Glan	d Dia	Α	l	В		С	l	D	
Cross-Section Outer	Inner	min max	min	max	min	max	min	max	
(mm2) (mm)	(mm)	(mm) (mm)							
Max 50 mm2 21	17	11	8	15	N/A	N/A	N/A	N/A	



## Schematic Diagram



## Enclosure Dimensions (\*)

Width	450 mm					
Length	380 mm					
Heigth	200 mm					
Weigth	20 kg					
Filling Compund (Optional)						
Volume	N/A					

<sup>\*</sup> Scheme and dimensions are not to be mentioned as final drawing. For exact dimensions, refer to technical drawing provided along with the Order Confirmation

<sup>\*\*</sup> Given are approximate values. Actual values might sligthly differ.