

CABLE PULLING HEAD



KEY FEATURES

- ✓ Ensures no damage or strain during pulling process
- ✓ Maintains tension and alignment during seabed cable-laying
- ✓ Extremely heavy duty and suitable for large underwater applications

Slingco's Pulling Head is designed to be used for subsea cable pull-ins, allowing a messenger line to be attached to the pulling head to guide the cable along the sea floor and up through a J tube for installation to a wind turbine.

Slingco Part No.	Cable diameter (mm)	Weight (kg/lb)
ZPH15107	90	53/117
ZPH15108	93	52.4/116
ZPH15109	97	51.7/114
ZPH15110	103	50.5/111
ZPH15111	104	64.9/143
ZPH15112	108	64/141
ZPH15113	116	62.1/137

Note

Note: Part Nos. ZPH15107–ZPH15110 and ZPH15111–ZPH15113 share a common outside geometry, respectively, and are machined internally to fit the required cable diameter.

This information is for marketing purposes only. The details contained herein is presented as general information and no representation or warranty is expressly or impliedly given as to its accuracy, completeness or correctness. It does not constitute part of a legal offer or contract. For technical specifications, please contact Slingco Limited.

Dimensions

The figures shown are indicative only. Fully dimensioned data-sheets are available on request. Nominal figures/actuals are as per data-sheet with tolerances of +/-5%. Please contact us if you have any questions.

Range dimension overlaps If the cable, rope or hose you have lies where ranges overlap, e.g. 1" when sizing is 0.5-1.00 and 1.00-1.5 we recommend that you select your cable grip to achieve break load first. If tensile strengths are equal or both adequate, choose the smaller of the two. Please contact us if you have any questions.